

BATTERY FOR PIGGING & OCEAN EQUIPMENT

DD-SC 100




MAIN CHARACTERISTICS

- ＼ 3.9V Li/SO₂Cl₂(Lithium Sulfuryl Chloride)
- ＼ 稳定的大功率供电及高能量密度
- ＼ 最小的初始放电电压下降现象(放电延迟现象)
- ＼ 保护电路(保险丝, 二极管)内装
- ＼ 取得ATEX认证(防爆认证)


标称容量(Capacity)	27Ah~32Ah
开路电压(OCV at 20°C)	3.91V
闭路电压(CCV at 25°C, 425mA)	3.4V
额定恒流/最大恒流(Constant Current)	580mA, 2,000mA
工作温度(Temperature)	-30°C to 100°C
直径(Diameter)	33.6mm (1.32 in)
高度(Height)	112.3mm (4.42 in)
重量(Cell Weight)	213g
锂重(Lithium Weight)	9.60g
保险丝(Safety Fuse)	7A
二极管(Bypass Diode)	200V/3A

D-SC 100



标称容量(Capacity)	12Ah~15Ah
开路电压(OCV at 20°C)	3.91V
闭路电压(CCV at 25°C, 200mA)	3.4V
额定恒流/最大恒流(Constant Current)	280mA, 1000mA
工作温度(Temperature)	-30°C to 100°C
直径(Diameter)	33.6mm (1.32 in)
高度(Height)	60.3mm (2.37 in)
重量(Cell Weight)	122g
锂重(Lithium Weight)	4.70g
保险丝(Safety Fuse)	4A
二极管(Bypass Diode)	200V/3A

C-SC 100



标称容量(Capacity)	4Ah~7Ah
开路电压(OCV at 20°C)	3.91V
闭路电压(CCV at 25°C, 80mA)	3.4V
额定恒流/最大恒流(Constant Current)	175mA, 600mA
工作温度(Temperature)	-30°C to 100°C
直径(Diameter)	25.5mm (1.00 in)
高度(Height)	49.1mm (1.93 in)
重量(Cell Weight)	59g
锂重(Lithium Weight)	2.40g
保险丝(Safety Fuse)	2A
二极管(Bypass Diode)	150V/1A

NOTE

＼ 电池的保险丝和二极管规格按照用户的使用条件能变更。